


TECHNICAL DETAILS

Type	Model	Power kW		Electric power supply	Fan motor kW	Gas connections
		min.	max.			
NG120	M-.TN.x.xx.A.0.15	60	120	230 V 1N ac	0,18	½"
NG140	M-.TN.x.xx.A.0.xx	60	170	230 V 1N ac	0,18	¾" - 1"
NG140	M-.xx.x.xx.A.0.xx	35	170	230 V 1N ac	0,18	¾" - 1"
NG200	M-.TN.x.xx.A.0.xx	85	200	230 V 1N ac	0,18	¾" - 1"
NG200	M-.xx.x.xx.A.0.xx	42	200	230 V 1N ac	0,18	¾" - 1"

For the configuration of the gas train, see page 101.



Type	Packaging dimensions (mm)			
	l	p	h	kg
NG120/140/200 S	600	370	400	25
NG120/140/200 L	750	370	400	25

Approximate values

Type	Model	Overall dimensions (mm)																								
		A	B		C		D	G	H	J	K	L	M	N	O		P	Q		R		S	T	W	X	Y
			min.	max.	min.	max.									min.	max.		min.	max.	min.	max.	min.				
NG120	M-.xx.S.xx.A.0.15	560	85	170	390	475	374	101	128	161	188	245	M8	188	109	158	133	382	467	202	287	180	32	537	340	Ø108
NG120	M-.xx.L.xx.A.0.15	660	85	270	390	575	374	101	128	161	188	245	M8	188	109	158	133	382	567	202	387	180	32	537	340	Ø108
NG140	M-.xx.S.xx.A.0.20	560	85	170	390	475	374	101	128	161	188	245	M8	188	109	158	133	382	467	202	287	180	32	537	340	Ø108
NG140	M-.xx.L.xx.A.0.20	660	85	270	390	575	374	101	128	161	188	245	M8	188	109	158	133	382	567	202	387	180	32	537	340	Ø108
NG140	M-.xx.S.xx.A.0.25	560	85	170	390	475	374	101	128	161	188	245	M8	188	109	158	133	426	511	202	287	224	32	565	340	Ø108
NG140	M-.xx.L.xx.A.0.25	660	85	270	390	575	374	101	128	161	188	245	M8	188	109	158	133	426	611	202	387	224	32	565	340	Ø108
NG200	M-.xx.S.xx.A.0.20	560	85	170	390	475	374	117	137	161	188	245	M8	188	109	158	133	382	467	202	287	180	32	537	340	Ø108
NG200	M-.xx.L.xx.A.0.20	660	85	270	390	575	374	117	137	161	188	245	M8	188	109	158	133	382	567	202	387	180	32	537	340	Ø108
NG200	M-.xx.S.xx.A.0.25	560	85	170	390	475	374	117	137	161	188	245	M8	188	109	158	133	426	511	202	287	224	32	565	340	Ø108
NG200	M-.xx.L.xx.A.0.25	660	85	270	390	575	374	117	137	161	188	245	M8	188	109	158	133	426	611	202	387	224	32	565	340	Ø108

Approximate values