


TECHNICAL DETAILS

Type	Model	Output kW		Auxiliary electrical power supply	Motor electrical power supply	Fan motor	Pump motor	Gas connections	Noise level
		min.	max.			kW	kW	Rp	dBA
G225X	MG.xx.xR.xx.A.1.xxx	230	2.250	230 V 1NAC 50 Hz	400 V 3 AC 50 Hz	5,5	1,1	2" - DN65 - DN80 - DN100	< 85
G270X	MG.xx.xR.xx.A.1.xxx	340	2.700	230 V 1NAC 50 Hz	400 V 3 AC 50 Hz	5,5	1,1	2" - DN65 - DN80 - DN100	< 85
G325X	MG.xx.xR.xx.A.1.xxx	620	3.250	230 V 1NAC 50 Hz	400 V 3 AC 50 Hz	7,5	1,1	2" - DN65 - DN80 - DN100	< 85

For the configuration of the gas train, see page 112-113.



Type	Packaging dimensions (mm)			
	l	p	h	kg
G225X	1680	1200	1050	325
G270X	1680	1200	1050	325
G325X	1680	1200	1050	330

Approximate values

Type	Model	Overall dimensions (mm)																																					
		AS	AL	AA	AB	AC	AD	AE	AN	AP	BS	BL	BB	C	CC	D	E	F	G	H	J	K	L	M	N	O		P	Q	R	S	U	V	W	Y	Z			
		min.		max.																																			
G225X	MG.xx.SR.xx.A.1.50	1360	1460	181	823	474	35	197	550	100	380	480	395	980	509	1198	725	473	259	290	450	380	518	M12	453	300	340	320	533	149	384	624	190	708	257	190			
G225X	MG.xx.SR.xx.A.1.65	1360	1460	181	823	474	35	197	564	117	380	480	395	980	509	1443	970	473	259	290	447	380	518	M12	453	300	340	320	636	149	487	845	292	708	257	190			
G225X	MG.xx.SR.xx.A.1.80	1360	1460	181	823	474	35	197	579	132	380	480	395	980	509	1475	1002	473	259	290	447	380	518	M12	453	300	340	320	687	149	538	875	310	708	257	190			
G225X	MG.xx.SR.xx.A.1.100	1360	1460	181	823	474	35	197	592	145	380	480	395	980	509	1558	1085	473	259	290	447	380	518	M12	453	300	340	320	791	149	642	942	353	708	257	190			
G270X	MG.xx.SR.xx.A.1.50	1401	1501	181	823	474	35	197	550	100	380	480	395	1021	509	1251	725	526	259	290	450	380	518	M12	453	300	340	320	533	149	384	624	190	708	257	190			
G270X	MG.xx.SR.xx.A.1.65	1401	1501	181	823	474	35	197	564	117	380	480	395	1021	509	1496	970	526	259	290	447	380	518	M12	453	300	340	320	636	149	487	845	292	708	257	190			
G270X	MG.xx.SR.xx.A.1.80	1401	1501	181	823	474	35	197	579	132	380	480	395	1021	509	1528	1002	526	259	290	447	380	518	M12	453	300	340	320	687	149	538	875	310	708	257	190			
G270X	MG.xx.SR.xx.A.1.100	1401	1501	181	823	474	35	197	592	145	380	480	395	1021	509	1611	1085	526	259	290	447	380	518	M12	453	300	340	320	791	149	642	942	353	708	257	190			
G325X	MG.xx.SR.xx.A.1.50	1451	1551	181	823	474	35	197	550	100	430	530	471	1021	509	1212	725	526	284	320	450	380	518	M12	453	300	340	320	533	149	384	624	190	708	257	190			
G325X	MG.xx.SR.xx.A.1.65	1451	1551	181	823	474	35	197	564	117	430	530	471	1021	509	1496	970	526	284	320	447	380	518	M12	453	300	340	320	636	149	487	845	292	708	257	190			
G325X	MG.xx.SR.xx.A.1.80	1451	1551	181	823	474	35	197	579	132	430	530	471	1021	509	1528	1002	526	284	320	447	380	518	M12	453	300	340	320	687	149	538	875	310	708	257	190			
G325X	MG.xx.SR.xx.A.1.100	1451	1551	181	823	474	35	197	592	145	430	530	471	1021	509	1611	1085	526	284	320	447	380	518	M12	453	300	340	320	791	149	642	942	353	708	257	190			

Approximate values