




TPBY TYPE TPBY90 ... TPBY3000

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

HEAVY OIL



Type	Min. modulation output kW	Min. application output kW	Max output kW
TPBY90	670	1.400	2.000
TPBY91	500	1.750	2.500
TPBY92	700	2.100	3.000
TPBY93	900	2.590	3.700
TPBY510	1.100	3.500	5.000
TPBY515	1.200	4.200	6.000
TPBY520	1.400	4.900	7.000
TPBY525	2.000	6.825	9.750
TPBY1030	2.550	9.310	13.300
TPBY1050	3.100	10.850	15.500
TPBY1080	3.800	13.300	19.000
TPBY2000	3.600	15.400	22.000
TPBY2500	4.500	18.400	27.000
TPBY3000	5.500	27.300	39.000

TECHNICAL DETAILS

Type	Model	Power kW		Pump motor	Resistor	Auxiliary electrical power supply	Motor electrical power supply
		min.	max.	kW	kW		
TPBY90	H-.xx.S.xx.G.xx	670	2.000	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY91	H-.xx.S.xx.G.xx	500	2.500	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY92	H-.xx.S.xx.G.xx	700	3.000	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY93	H-.xx.S.xx.G.xx	900	3.700	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY510	H-.xx.S.xx.G.xx	1.100	5.000	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY515	H-.xx.S.xx.G.xx	1.200	6.000	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY520	H-.xx.S.xx.G.xx	1.400	7.000	0,75	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY525	H-.xx.S.xx.G.xx	2.000	9.750	1,1	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY1030	H-.xx.S.xx.G.xx	2.550	13.300	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY1050	H-.xx.S.xx.G.xx	3.100	15.500	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY1080	H-.xx.S.xx.G.xx	3.800	19.000	1,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY2000	H-.xx.S.xx.G.xx	3.600	22.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY2500	H-.xx.S.xx.G.xx	4.500	27.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
TPBY3000	H-.xx.S.xx.G.xx	5.500	39.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz