




TECHNICAL DETAILS

Type	Model	Power kW		Electric power supply	Fan motor kW	Pump motor kW	Gas connections
		min.	max.				
HS5	MG.TN.x.xx.A.0.15	35	70	230 V 1N ac	0,10	0,1	1/2"
HS10	MG.TN.x.xx.A.0.20	65	140	230 V 1N ac	0,15	0,1	3/4"
HS18	MG.TN.x.xx.A.0.25	80	200	230 V 1N ac	0,15	0,1	1"



Type	Packaging dimensions (mm)			
	l	p	h	kg
HS5	580	580	360	23
HS10	510	350	730	30
HS15	510	350	730	31

Approximate values

Type	Model	Overall dimensions (mm)								Boiler drilling (mm)				Burner flange (mm)		
		A	B	BL	C	CL	D	G	L	H	M	N	P	K	O	
													min. max.		min. max.	
HS5	MG.TN.x.xx.A.0.15	320	0÷61	0÷160	380	480	400	80	190	90	M8	130÷189	92 134	162	86	138
HS10	MG.TN.x.xx.A.0.20	351	159	254	510	605	430	108	210	115	M8	148÷189	105 134	162	103	103
HS18	MG.TN.x.xx.A.0.25	348	177	267	525	615	430	126	210	135	M8	148÷189	105 134	162	103	103

Approximate values